


# Federstecker verzinkt


## einfache Ausführung

| Nenngröße | für Bolzen-Ø | Abmessungen |     |     |    | Gewicht pro %Stück | Preis pro Stück |      |      |
|-----------|--------------|-------------|-----|-----|----|--------------------|-----------------|------|------|
|           |              | d1          | d4  | d2  | d3 |                    | l1              | l2   | VPE  |
| mm        | mm           | mm          | mm  | mm  | mm | mm                 | kg              | VPE  | Euro |
| 2         | 9-14         | 10          | 2,5 | 50  | 25 | 0,3                | 250             | 0,10 |      |
| 3         | 10-16        | 18          | 3,5 | 60  | 28 | 0,9                | 250             | 0,20 |      |
| 4         | 16-20        | 20          | 4,5 | 60  | 30 | 1,6                | 100             | 0,25 |      |
| 5         | 20-28        | 24          | 6,0 | 85  | 40 | 3,3                | 100             | 0,40 |      |
| 6         | 28-40        | 30          | 7,0 | 105 | 50 | 6,2                | 50              | 0,75 |      |
| 7         | 28-45        | 30          | 8,0 | 105 | 50 | 8,3                | 25              | 1,20 |      |
| 8         | 30-45        | 28          | 9,0 | 110 | 55 | 10,5               | 25              | 1,60 |      |



## doppelte Ausführung

| Nenngröße | für Bolzen-Ø | Abmessungen |     |     |    | Gewicht pro %Stück | Preis pro Stück |      |      |
|-----------|--------------|-------------|-----|-----|----|--------------------|-----------------|------|------|
|           |              | d1          | d4  | d2  | d3 |                    | l1              | l2   | VPE  |
| mm        | mm           | mm          | mm  | mm  | mm | mm                 | kg              | VPE  | Euro |
| 2         | 8-14         | 10          | 2,5 | 50  | 25 | 0,4                | 250             | 0,15 |      |
| 3         | 14-20        | 16          | 3,5 | 62  | 32 | 1,4                | 250             | 0,20 |      |
| 4         | 17-24        | 23          | 4,5 | 78  | 44 | 3,0                | 100             | 0,45 |      |
| 5         | 18-30        | 26          | 5,5 | 92  | 50 | 5,3                | 50              | 0,70 |      |
| 6         | 24-36        | 30          | 6,5 | 120 | 70 | 9,6                | 25              | 1,10 |      |
| 7         | 24-40        | 30          | 8,0 | 130 | 72 | 13,5               | 25              | 1,85 |      |
| 8         | 24-45        | 30          | 9,0 | 130 | 76 | 17,8               | 25              | 2,40 |      |



# Klappsplinte

## Standard, verzinkt

| Nenngröße | max. Bolzen-Ø | Abmessungen |      |     |      | Gewicht pro %Stück | Preis pro Stück |      |
|-----------|---------------|-------------|------|-----|------|--------------------|-----------------|------|
|           |               | c           | d    | f   | l    |                    | VPE             | Euro |
| mm        | mm            | mm          | mm   | mm  | mm   | kg                 | VPE             | Euro |
| 4,5       | 34            | 34          | 4,5  | 3,4 | 34,0 | 2,0                | 50              | 0,35 |
| 6,0       | 38            | 41          | 6,0  | 3,4 | 42,0 | 2,8                | 50              | 0,40 |
| 7,0       | 38            | 41          | 7,0  | 3,4 | 42,0 | 3,0                | 50              | 0,45 |
| 8,0       | 38            | 41          | 8,0  | 3,4 | 42,0 | 3,5                | 50              | 0,50 |
| 9,0       | 38            | 41          | 9,0  | 3,4 | 42,0 | 3,8                | 50              | 0,60 |
| 10,0      | 38            | 41          | 10,0 | 3,4 | 42,0 | 4,4                | 50              | 0,60 |
| 11,0      | 38            | 41          | 11,0 | 3,4 | 42,0 | 4,6                | 50              | 0,65 |

